



REM Grain Vac CAPACITIES & SPECIFICATIONS

CAPACITIES

Rem 2700 GrainVac

Rem 3700 GrainVac

CORN	Rem 2700 GrainVac	Rem 3700 GrainVac
8 ft (2.4m)	6,000 bu/hr (150 t/h)	10,000+ bu/hr (250+ t/h)
24 ft (7.3m)	3,200 bu/hr (80 t/h)	8,000 bu/hr (200 t/h)
50 ft (14.6m)	2,200 bu/hr (56 t/h)	5,000 bu/hr (120 t/h)
WHEAT		
8 ft (2.4m)	5,000 bu/hr (135 t/h)	10,000 bu/hr (270 t/h)
24 ft (7.3m)	2,100 bu/hr (57 t/h)	8,000 bu/hr (215 t/h)
50 ft (14.6m)	1,400 bu/hr (38 t/h)	5,000 bu/hr (135 t/h)
CANOLA		
8 ft (2.4m)	5,000 bu/hr (110 t/h)	9,500 bu/hr (215 t/h)
24 ft (7.3m)	4,000 bu/hr (90 t/h)	8,000 bu/hr (180 t/h)
50 ft (14.6m)	2,600 bu/hr (58 t/h)	5,000 bu/hr (112 t/h)

Results may vary depending on conditions and hose configuration.

PTO UNIT SPECIFICATIONS

Rem 2700 GrainVac

Rem 3700 GrainVac

Weight	2900 lbs (1315 kg)	4300 lbs (1950 kg)
Hitch Weight	400 lbs (181 kg)	430 lbs (218 kg)
Auger Discharge Height	14' (4.25 m)	16' (4.9 m)
Hydraulic Requirements	2 GPM flow rate @ 2100 PSI	2 GPM flow rate @ 2100 PSI
Tractor HP Requirements	85 PTO HP @ Full Bin Loadout	160 - 180 PTO HP @ Full Bin Loadout

STANDARD HOSE CONFIGURATIONS

Rem 2700 GrainVac

Rem 3700 GrainVac

1-Stainless steel flexible hose	7"x 29" (18 cm x 0.7 m)	8"x 36" (20 cm x 0.9 m)
2-Stainless steel flexible hoses	7"x 80" (18 cm x 2 m)	8"x 96" (20 cm x 2.4 m)
2-Aluminum Pipes	7"x 87" (18 cm x 2.2 m)	8"x 96" (20 cm x 2.4 m)
1-Aluminum Pipe	7"x 54" (18 cm x 1.3 m)	8"x 60" (20 cm x 1.5 m)
1-Flexible rubber clean-up hose	7"x 81" (18 cm x 2 m)	8"x 81" (20 cm x 2 cm)
1-Telescoping Tube	N/A	8"x 25" - 38" (20 cm x 63 cm - 96 cm)
1-Floor sweep	7" Standard	8" Standard
1-Aluminum Bin Load-out Nozzle	7"x 36" (18 cm x 91 cm)	
1-Clean-up nozzle with wheels	7" (18 cm)	



431 Gosport Street Moree
 Phone – 02 67521511 Fax – 02 67524685
 email - andrew@grainland.com.au
www.grainland.com.au